

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-293249

(43)Date of publication of application : 20.10.2000

(51)Int.Cl.

G05G 1/14
B60T 7/02
G05G 25/00

(21)Application number : 11-094529

(71)Applicant : NISSAN MOTOR CO LTD

(22)Date of filing : 01.04.1999


(72)Inventor : KAWAHARA SADAHIRO
UEDA YASUHIRO

(54) PEDAL LEVER DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To increase the degree of freedom of a layout by putting the fitting position of stopper rubber close to the center of rotation of a pedal lever by forming a recessed part at the part which abuts against the operation element of the stopper rubber.

SOLUTION: A nearly L-shaped bracket 6 equipped with the stopper rubber 5 on the surface inside a cabin is fixed to the upper end part of the brake pedal lever 1. The stopper rubber 5 has the recessed part 13 formed at the part which abuts against the operation element 12 of a stop lamp switch 7 when the brake pedal lever 1 is stepped in, the operation element 12 is released from being pressed and the stop lamp switch 7 turns ON, so that the stop lamp illuminates. Here, the fitting position of the stop lamp switch 7 is so adjusted that the interval between the tip of the screw part 9 of the stop lamp switch 7 and the surface of the stopper rubber 5 has a specific value. Namely, the movement quantity of the stopper rubber 5 is the depth of the recessed part 13 less than usual.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

KSR 003089

BEST AVAILABLE COPY